SCREWED END
3 WAY, MOUNTING PAD, REDUCED PORT

SIZE: 1/4"~3"





STAINLESS STEEL
AISI-316 (EN10213-4 1.4408) (ASTM-A351-CF8M)
AISI-304 (EN10213-4 1.4308) (ASTM-A351-CF8)
CARBON STEEL
S-20C (EN10213-2 1.0619) (ASTM-A216-WCB)

FEATURES:
*Pipe thread in accordance with ANSI B2.1, BS 21 1973, DIN 259/2999, ISO 228
*Blow-out proof stem
*Investment casting body and cap
*1000 WOG (63 BAR)
*Mounting Pad ISO 5211
*L port, T port


OPTION: Anti-static device
Locking device
Direct mounting pad ISO 5211 (Reduced & Full port, Anti-static device)
Mounting pad for ISO 5211 (Reduced & Full port)
No mounting pad (Reduced port only)

ITEM	PARTS	MATERIALS
1	BODY	ASTM-A351-CF8M
2	CAP	ASTM-A351-CF8M
3	SEAT	15% R-PTFE
4	BALL	ASTM-A351-CF8M
5	STEM	AISI316
6	END SEALS	PTFE
7	THRUST WASHER	PTFE
8	GLAND	AISI304
9	HANDLE	AISI304
10	HANDLE WASHER	AISI304
11	WASHER	AISI304
12	HANDLE NUT	AISI304
13	HANDLE SLEEVE	PLASTIC
14	END CAP	ASTM-A351-CF8M
15	STEM PACKINGS	PTFE
16	END SEALS	PTFE
17	STOP PIN	AISI304
18	BOLT	AISI304





PORT / TYPE	1	2	3	4
L	1 2 3	1 2 3	1 2 3	1 2 3
T	1 2 3	1 2 3	1 2 3	1 2 3



DIMENSIONS UNIT:mm

NOMINAL SIZE	d±0.2	L±0.8	H±1.0	D1±1.0	A	B	C	D	E	F	M	N
1/4"	11.0	69.4	60.7	133.4	10.7	5.7	12	9	29.7	34.6	42	M5*0.8
3/8"	11.0	69.4	60.7	133.4	10.7	5.7	12	9	29.7	34.6	42	M5*0.8
1/2"	12.5	75.7	64.1	133.4	10.7	5.8	12	9	29.7	37.25	42	M5*0.8
3/4"	16.0	86.6	82.4	178.5	13.9	6.9	15	11	35.4	44.7	50	M6*1
1"	20.0	102.	86.1	178.5	20.0	8.5	15	11	35.4	51.4	50	M6*1
1-1/4"	25.0	118.2	91.4	209.9	23.8	7.8	15	11	35.4	57.7	50	M6*1
1-1/2"	32.0	125.8	102.7	208	25.8	10.2	15	11	49.5	62.7	70	M8*1.25
2"	38.0	149	110.7	229.9	25.3	9.7	18.5	14	49.5	74.6	70	M8*1.25
2-1/2"	50	160	132	265	24.5	8.5	18.5	14	49.5	80	70	M8*1.25
3"	65	185	132	265	29	90.	21.0	17	72.1	92.5	102	M10*1.5